

IP CAMERAS 2MP Dome IP CAMERA WDD20IP12A

WatchDog's Best in Class IPcameraseries is aimed to provide high quality surveillance as an affordable offering for the small and medium businesses including small retail shops, gyms, schools, residential homes, Offices etc.

The new series includes 2 MP IR cameras in both Dome and bullet configurations with fixed and variable lens options to cater to all kinds of customer applications. The cameras come with IR LEDs so as to provide effective and efficient surveillance even during the night time. The cameras are IP66/IP67 rated that makes them resilient for outdoor applications as well



Figure 1 WDD20IP12A



Sensor



Min. Illumination



DWDR



Motion Detection





AWB



AGC



KEY FEATURES

- · 2MP full real time recording
- Max resolution: 1920 X 1080
- SD Card Support upto 128 GB
- Upto 30m IR distance
- 3D DNR, WDR 120dB
- IP 67
- Support Tripple streams
- Onvif Profile S/Gcompliant

WATCHDOG 2 MP IP BULLET CAMERAS

SPECIFICATIONS: WDD20IP12A

Model NO.	WDD20IP12A
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Resolution	2MP
Effective Pixels	3864(H)*2192(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/30- 1/10000Sec
Minimun Illumination	0.001Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
Lens	
Focus Length	2.7-13.55 mm Motor Zoom
Focus Control	Auto
Lens Type	Auto
Pixels	1080P
Night Vision	
Infrared LED	42μ x 6PCS
Infrared Distance	80M
IR Status	Auto Control
IR Power On	Smart, Manual & Timed mode
Network	<u> </u>
Ethernet	RJ-45 (10/100Base-T)
Wireless	/
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, UDP
ONVIF	Support ONVIF 2.4(Profile S/T/G)

P2P	YES, Support QR Code
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	1920*1080@30fps
Main Stream 2	960@30fps
Main Stream 3	720@30fps
Tri Stream	1280*720@30fps 720*480@30fps 352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox , Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Al Function	
Intelligent Analysis	Face Detection, Intrusion Detetion, Line Cross Detetion, Loiter Detetion, People Gather Detecion
Camera Feature	S
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR, White Balance, FLK(Flicker Control), Video Tampering, HLC, Distortion
Full Color	/
Corridor Pattern	Support
Defog Mode	Support
ROI	Support
BLC	Support
WDR	HDR: 120dB
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands, Czech, Vietnamese
Interface	
	Comment A. D. L. 170 co. c.
Audio	Support Audio Input/Output
Alarm	Support 1 Channel Input/Ouput
SD Card Slot	External, Support Max 128 GB
RS485	/

General		
Housing	IP67	
Anti-cut Bracket	YES	
IR Cut Filter	YES	
Operation Temperature	-20°C ~ +60°C RH95% Max	
Storage Temperature	-20°C ~ +60°C RH95% Max	
Power Source	DC12V±10%,1100mA	
Dimension	220(W) x 109(H) x 106(D)mm	
Weight	2.15Kgs	

For More Information info@mywatchdog.in

Apollo Infoways Private Limited G-149, Sector -63 Noida, U.P. 201301 Ph: 0120-4122342 (4 Lines) www.mywatchdog.in

CEFC V

@2019 Apollo Infoways Pvt. Ltd.