

IP CAMERAS 2MP BOX TYPE IP CAMERA WDB20MIPNPR

WatchDog's Best in Class IP camera series is aimed to provide high quality surveillance as an affordable offering for the small and medium businesses including small retail shops, gyms, schools, residential homes, Offices, Traffic etc.

The new series includes 2MP IR cameras in both Dome and bullet configurations with fixed and variable lens options to cater to all kinds of customer applications. The cameras come with IR LEDs so as to provide effective and efficient surveillance even during the night time. The cameras are IP66/IP67 rated that makes them resilient for outdoor applications as well



Figure 2 WDB20MIPNPR



KEY FEATURES

- 2MP full real time recording
- True day night function
- Upto 80m IR distance
- 3D DNR, WDR 140dB
- Supports Global Shutter
- Alarm I/O: 2
- Audio : In/Out
- Support triplestreams
- Onvif Profile S/G/T/M compliant

WATCHDOG BOX IP CAMERAS

SPECIFICATIONS: WDB20MIPNPR

| | |
|--|---|
| CAMERA | |
| Image Sensor | 1/ 1.8" , CMOS sensor |
| Number of Pixels (H x V) | 1920 X 1080 @60fps |
| Electronic Shutter | 1/25s ~ 1/ 100000s |
| Iris | Auto Iris |
| Min Illumination | 0.005 lux @F1.2, AGC ON; 0 lux with IR |
| Lens | Veri-Focal 5 - 50 mm , Angle of View: 'H:54.72° (Wide)~5.40° (Tele)/ V: 32.19° (Wide)~3.00° (Tele)/D: 61.4(Wide)~6.06(Tele) |
| Day & Night | True Day Night |
| Wide Dynamic Range | ≥140dB |
| IMAGE | |
| Video Compression | H.265/H.264 / MJPEG |
| Compression Standard | Baseline / Main / High Profile |
| Lens/ Barrel Distortion Correction & Corridor View | In-built |
| Memory | RAM-1GB, Flash-256MB |
| Resolution | Main stream: 1920 x 1080, 1280 x 720 Sub stream: 704 x 576 , 352 x 288 Third stream: 704 x 576 , 480 x 240 , 352 x 288 |
| Bit Rate | Main stream: 1024 ~ 6144 Kbps Sub stream: 256 ~ 1536 Kbps Third stream: 128 ~ 1024 Kbps |
| Encode Mode | CBR / VBR (Freely adjustable in CBR, 5 levels in VBR) |
| Image Settings | ROI, Saturation, Brightness, Contrast, Wide Dynamic, Sharpen, Noise reduction |
| ROI | 3 ROI |
| INTERFACES | |
| Network | RJ45 |
| SECURITY | |
| User Authentication | HTTP/HTTPS Authentication, Digest Login authentication, IP Address Filtering, User access Log,802.1X Authentication |
| FUNCTIONS | |
| Remote Monitoring | IE / Firefox Browsing, CMS/VMS control |
| Storage | SD Card 256 GB/ NAS |
| Network Protocol | IPv4,IPv6,TCP/IP, UDP/IP,RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, UPnP, Bonjour FTP, SMTP, ICMP, IGMP, SNMP, ARP, DNS, DDNS, QoS |
| Intelligent Analysis | Motion Detection, Face Detection, Intrusion Detection, Line Cross Detection, Loiter Detection, People Gather Detection, Number Plate Recognition etc. |
| Audio Compression | G.711, G.726 |
| Interface Protocol | ONVIF S, ONVIF G, ONVIF T, ONVIF M |
| Signal to Noise Ratio | ≥ 65 dB |
| IR Distance | 80 m |
| Housing | IP67, IK10, NEMA-TS |
| OTHERS | |
| Power Supply | DC 12V,PoE |
| Power Consumption | <4 W |
| IR Consumption ON | <7 W |

| | |
|-----------------------|-------------------------------------|
| Operating Temperature | -40 deg C to 60 deg C, 90% humidity |
| Dimensions (mm) | 87 x 219 |
| Weight | 2500 g |
| Certifications | CE, FCC, RoHS, EN, BIS Certified |
| Country of Origin | Made In India |

For More Information
info@mywatchdog.in

Apollo Infoways Private Limited
G-149, Sector -63
Noida, U.P. 201301
Ph: 0120-4122342 (4 Lines)
www.mywatchdog.in

